

## Speco Control Series Wall & Ceiling Mountable, Weather/ Tamper Resistant IR Dome Cameras

HTD8SCSC HTD8SCSB HTD8SCSW

chrome housing

black housing

white housing

## Features OSD Control of All Major Camera Functions

- Exposure Control Shutter Speed, AGC, HLC, Back Light Compensation and Wide Dynamic Range
- · White Balance ATW, Fixed, Manual and AWB
- Day/Night Select Color, B/W or Auto Select
- · Mirror Image Horizontal and Vertical
- Privacy Screens Up to 4 zones



## **Specifications**

Image Device (Image Sensor)	1/3" Sony Super HAD™ CCD
Built-in Lens	2.8-12mm
Resolution	540 TV Lines
Total Pixels	811(H) x 508(V)
Effective Pixels	768(H) x 494(V)
Iris	DC Auto Iris
Electronic Shutter Speed	1/60 ~ 1/100,000 sec.
Color	Yes
Minimum Object Illumination	0.00 Lux (w/full LEDs)
Number of IR LED	48
LED IR Wave Length	850nm
Effective IR Range	150'
Video S/N Ratio	50dB (Weight On)
Gamma	On/Off adjustable
Video Signal Output	1.0V [p-p] Composite, 75Ω
Scanning System	2:1 Interlaced 525 lines/60 fields/
	30 frames
Synchronization System	Internal
Back Light Compensation	On/Off Adjustable
AGC	On/Off
CDS Sensor	Yes

TV System	NTSC
Motion Detection	On/Off (4 programmable zones)
Privacy Function	On/Off (4 programmable zones)
White Balance	ATW/AWB/Fixed/Manual
Gain Control	On/Off
DNR (Digital Noise Reduction)	On/Off
OSD (On Screen Display)	Built-in
BLC/HLC (Back/High Light	
Compensation	Yes
Day & Night	Color/B&W/Auto selectable
Operating Temperature	20°F~122°F
Storage Temperature	38°F~122°F
Operating Humidity	30% - 90% RH
Weatherproof IP Rating	IP65
Power Consumption (AC/DC)	DC12V only
Power Requirement (Voltage)	DC12V (600mA)
Unit Construction Materials	Metal
Indoor/Outdoor	Indoor/Outdoor
Dimensions	2.4" Dia. x 3.65" H
Weight	
Included in Box	Mounting Hardware

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 5/10/11